

specifications

| | |
|--|--|
| Digital to Analogue conversion | 24-bit multilevel Delta-Sigma DAC |
| Laser pick-up | 3 beam |
| Laser wavelength | 780nm |
| Numerical aperture | 0.45 |
| Signal to noise ratio | 109dB (20Hz–20kHz bandwidth) |
| Harmonic distortion (1kHz) | 0.002% |
| Frequency response (± 0.5 dB) | 0.3Hz–20kHz |
| Output level (0dB) | 2.3Vrms |
| Output impedance | 47 Ω |
| Minimum recommended load | 5k Ω |
| Physical | |
| Dimensions | W430 x D355 x H85mm |
| Weight | 6.2kg nett/8.0kg packed |
| Power consumption | 32VA maximum |
| Digital output connection | 75 Ω co-axial optical TOSLINK |
| Supplied accessories | |
| | Mains lead CR90 remote control 2 x AAA batteries |
| E&OE | |
| NOTE: All specification values are typical unless otherwise stated. | |

Continual improvement policy

Arcam has a policy of continual improvement for its products. This means that designs and specifications are subject to change without notice.

Radio interference

The CD37 compact disc player is a digital audio device which has been designed to very high standards of electromagnetic compatibility.

All CD players generate, and can radiate RF (radio frequency) energy. In some cases this can cause interference with FM and AM radio reception. If this is the case, keep the CD player and its connecting cables as far from the tuner and its aerials as possible. Connecting the CD player and the tuner to different mains sockets can also help to reduce interference.

EC COUNTRIES – This products have been designed to comply with EMC Directive 2004/108/EC.

USA – These products comply with FCC Part 15 Class B.

Laser radiation

**CLASS I
LASER PRODUCT**

If the CD37 compact disc player is operated whilst the outer casing is removed, invisible laser radiation could cause eye damage.