

TECHNICAL SPECIFICATIONS

DVD PLAYER FMJ DV139

Video Outputs

Composite Video

S-Video

Component Video

SCART Socket with RGB video

1 x Gold plated phono: IV pk-pk into 75Ω

1 x 4 pin mini DIN: Y IV pk-pk 75Ω, C 0.3V pk-pk into 75Ω

Interlaced or Progressive

3 Gold plated phono sockets: Y IV pk-pk into 75Ω;

Pb 0.7V pk-pk into 75Ω; Pr 0.7V pk-pk into 75Ω

All 0.7V into 75Ω, composite video IV into 75Ω and stereo audio.

Auto switching of TV with aspect ratio control

HDMI

19-pin HDMI connector

Supported video formats are:

720x576p, 720(1440)x576i, 720x480p,

720(1440)x480i, 1280 to 720p, 1920 x 1080i,

1920 x 1080p

audio to 6-channel/96kHz or 2-channel//192kHz (24-bit).

Audio Outputs

Analogue audio outputs

Output level

Frequency response

THD+N

Signal to noise ratio

Digital audio output (IEC958)

Stereo or multi-channel output on gold-plated phono sockets

2.2V rms at 0dB signal, 4V rms with HDCD discs (left and right channels only)

20Hz to 20kHz (+0.1db. -0.5db)

<0.005% for 1kHz 0db signal, measured from 22Hz-22kHz, unweighted

105dB, measured 20Hz-20kHz, unweighted

PCM/Dolby digital/MPEG/DTS on gold plated phono (coax) and TOSLINK (optical)

Disc types replayed

DVD-Video, DVD Audio, SACD version 1.3,

MPEG2, MPEG4 (DivX) encoding, Dolby

Digital 5.1, DTS 5.1, CD Video, SVCD, CD-

Audio (inc. CD-R, CD-RW) with PCM, HDCD

WMA or MP2, MP3 and OGG encoding, DVD-

R, DVD-RW, DVD+R, DVD+RW, JPEG image

files on CD (Picture CDs) and DVD

General

Power consumption

Size w/d/h mm. Inc. feet

Weight (net)

<35 VA

435 x 355 x 87

5.1kg