

Technical specifications

General	
Power Requirements	Within the range 115V to 230V AC
Power consumption	< 35 VA
Dimensions	435mm x 80mm x 350mm
Weight	net: 5.2kg; packed: 8.0kg
Audio outputs	
Analogue audio outputs	Four zones of stereo output on gold-plated phono sockets
Output level	2.2V rms at 0dB signal
Frequency response	20Hz to 20kHz (+0.1db, -0.5dB)
THD+N	<0.005% for 1kHz 0dB signal, measured 22Hz-22kHz, unweighted
Signal-to-noise ratio	105dB, measured 20Hz-20kHz, unweighted
Digital audio output (IEC958)	PCM on gold-plated phono (coax) and TOSLINK (optical) sockets
Video outputs	
Composite video	1 x gold plated phono. 1V pk-pk in 75Ω
S-Video	1 x 4-pin mini-DIN. Y 1V pk-pk in 75Ω, C 0.3V pk-pk in 75Ω
VGA	SVGA output (800 x 600 pixels, up to 16 million colours) 1 x 15-pin D-subminiature VGA connector
Accessories supplied	
	CR-425 Remote control
	2 x AAA batteries
	mains lead
E&EO	

NOTE: All specification values are typical unless otherwise stated.

Continual improvement policy

Arcam has a policy of continual improvement for its products. This means that designs and specifications are subject to change without notice.