

MOON CD-1 CD Player

Specifications

Configuration	Single-ended
Power Supply Transformer	25VA
Power Supply Capacitance	13,200 μ F
Transport Mechanism	Proprietary Design
Digital Filter / Digital-to-Analog Converter	BurrBrown PCM1793
Frequency Response (audible)	20Hz - 20kHz +0/-0.2dB
Frequency Response (full range)	2Hz - 72kHz +0/-3dB
THD @1kHz, 0dBFS (A-weighted)	< 0.002%
Intermodulation Distortion	< 0.005%
Dynamic Range	> 110dB
Signal-to-noise Ratio	> 110dB @ full output
Slew Rate	50V/ μ s
Channel Separation	> 106db
Low Level Linearity	$\pm$ 1.0dB to below 120dbFS
Intrinsic Jitter	< 300 picoseconds RMS
Analog Output - Standard	1 pair Single-ended RCA's
Analog Output Impedance - Standard	100 Ω
Max. Analog Output @ 0dBFS - Standard	2.0 Volts RMS
Digital Output	S/PDIF RCA
Digital Output Impedance - S/PDIF	75 Ω (0.5 Volts)
Standard Remote Control	Full-Function
Power Consumption @ idle	15 Watts
AC Power Requirements	120V / 60Hz or 240V / 50Hz
Shipping Weight	14 lbs / 6.25 Kgs
Dimensions (W x H x D, inches)	16.9 x 3 x 12.75



Fuse Replacement:

For the 120V version use a 0.2A slow blow (5 x 20mm size).
For the 230V version use a 0.1A slow blow (5 x 20mm size).