



SRT 5440

HDTV

**PVR Ready via External USB HDD
Time Shift, Record & Playback
USB 2.0 Host for PC Interface &
File Transfer
MP3 Playback & JPEG Viewing**

- 1080i / 720p / 576p / 576i Video Formats
- HDMI Output
- VFD Display
- Component Video: Y, Pb & Pr Outputs
- Dolby Digital Optical Output
- RGB Output through SCART
- 16:9 Full Screen, 4:3 Letterbox & Full Screen
- Electronic Program Guide
- Closed Captions & Teletext
- Auto & Manual Channel Search
- Favourite Channel List
- DVB/T, MPEG-2/4, H.264 Compliant
- COFDM Demodulation

HIGH DEFINITION DIGITAL TERRESTRIAL TELEVISION RECEIVER



 ***STRONG***

not just by name



SRT 5440 SPECIFICATIONS



TUNER

Guard Internal Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration	Signal Level	: -78.5 - -25dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance	: 75Ω
Input Connector	: IEC 169-2, Female	Wave Form	: OFDM
Frequency Range	: 170-860MHZ	Carrier Mode	: 2K & 8K
Demodulator	: COFDM 2K/8K-Carrier		
Channel Bandwidth	: 7/8MHz Switchable by Software		

MPEG TS A/V Decoder

Transport Stream	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
Profile Level	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
	: MPEG-IV AVC/H.264 HP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i	Input Rate	: Max. 15 Mbit/s
	Selectable		
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

A/V Input/Output

TV SCART Video Output	: CVBS & RGB, Audio Output L & R	Video Output	: RCA/Cinch
VCR SCART	: A/V Output: CVBS, L/R		: Component Output, Y, Pb, Pr
	: A/V Input CVBS, RGB, L/R		: S-Video
Digital A/V Output	: HDMI 1.2 (High Definition Multimedia Interface)	Audio L/R	: RCA/Cinch
S/PDIF	: Optical Digital Audio Output		

Data Input/Output

RS-232C	: Transfer Rate 115Kbps, 9 PIN D-Sub Type
USB	: 2.0 Host

System Resources

Main Processor	: 32bit Super Scalar RISC CPU
Flash ROM	: 64Mbit
DDR DRAM	: 256Mbit
EEPROM	: 256Kbit

Power Supply

Input Voltage	: AC 100-250V~, 50/60Hz	Power Consumption:	Max. 40 W
Type	: SMPS (Switching Mode Power Supply)	Protection	: Separate Internal Fuse

Physical Specifications

Size (W x D x H)	: 335 x 247 x 58.8 mm
Weight	: 2.3 Kg
Operating Temperature	: 0°C ~ +45°C
Storage Temperature	: -10°C ~ +70°C

E. & O. E.

DISTRIBUTED BY:



STRONG TECHNOLOGIES PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA
PH: +61 3 8795-7990 FAX: +61 3 8795-7991

TECHNICAL SUPPORT: 1 800 820 030

STRONG & CO. (FAR EAST), LTD. - P. O. BOX 85, YOKOHAMA, KANAGAWA-KEN, JAPAN 231-91 - FAX: +81 45 651-1842

www.strong-technologies.com

E-mail: salesau@strong-technologies.com