



## ***SRT 5490***



- 250 GB Hard Disk Drive**
- 30 Hours HD or 125 Hours SD Recording**
- Simultaneous Recording and Playback**
- Time Shift**
- Timer Recording**
- Picture-in-Picture**
- USB 1.1 for PC Interface & File Transfer**
- Lan Port for PC Communication & File Transfer**
- MP3 Playback & JPEG Viewing**

- 1080i / 720p / 576p / 576i Video Formats
- Format Change by Remote Control
- DVI-I Digital Video Interface
- Component Video (Y, Pb & Pr) Outputs
- RGB-HV / RGB Component (VGA) Output
- Dolby Digital Optical & Coaxial Outputs
- 16:9 Full Screen, 4:3 Letterbox & Full Screen
- Zoom Mode by Remote Control Hot Key
- Auto & Manual Channel Search
- Favourite Channel List
- Electronic Program Guide
- Preprogrammed STB/TV Remote Control
- Closed Captions & Teletext
- DVB/T, MPEG-2 Compliant
- COFDM Demodulation



[www.strong-technologies.com](http://www.strong-technologies.com)

## **DIGITAL TERRESTRIAL TELEVISION RECEIVER**



# **STRONG SRT 5490 SPECIFICATIONS**



## **TUNER**

|                      |   |
|----------------------|---|
| Guard Internal Modes | : 1/32, 1/16, 1/8, 1/4 Active Symbol Duration |
| FEC Modes Rates      | : 1/2, 2/3, 3/4, 5/6, 7/8                     |
| Input Connector      | : IEC 169-2, Female                           |
| Frequency Range      | : 170 - 860 MHz                               |
| Demodulator          | : COFDM 2K/8K-Carrier                         |
| Channel Bandwidth    | : 7MHz (for Australia)                        |

## **MPEG TS A/V DECODER**

|                  |  |
|------------------|--|
| Video Resolution | : 1080i / 720p / 576p / 576i for 25Hz Selectable |
| Audio Mode       | : Single / Dual Channel                          |
| Transport Stream | : MPEG-2 ISO/IEC 13818-1                         |
| Audio Decoding   | : AC-3, MPEG/Musical Layer 1 & 2                 |

## **A/V & DATA INPUT/OUTPUT**

|       |  |
|-------|--|
| Video | : Y, Pb, Pr - Component<br>: DB15p (RGBHV)<br>: DVI-I<br>: 4 Pin Mini Din Connector - SVHS   |
| Audio | : RCA/Cinch (CVBS)<br>: S/PDIF of Dolby Digital.TOS-LINK & Coaxial (RCA)<br>: RCA (Variable) |

## **COMMUNICATION**

|               |                                    |
|---------------|------------------------------------|
| USB Port      | : USB V1.1 Interface               |
| Ethernet Port | : IEEE 802.3, 10/100Mbps Interface |

## **SYSTEM RESOURCES**

|        |                                       |
|--------|---------------------------------------|
| PVR    | : Hard Disk Drive 250GB               |
| Memory | : 128 Mbyte DRAM / 16Mbyte NAND Flash |
| CPU    | : 300MHz 32bit MIPS                   |

## **POWER SUPPLY**


|               |                          |                   |             |
|---------------|--------------------------|-------------------|-------------|
| Input Voltage | : AC 98~240V - 47-63Hz   | Power Consumption | : Max. 35 W |
| Protection    | : Separate Internal Fuse | Type              | : SMPS      |

## **PHYSICAL SPECIFICATIONS**

|                       |                        |
|-----------------------|------------------------|
| Size (W x H x D)      | : 360mm x 65mm x 290mm |
| Net Weight            | : 3.6 Kg               |
| Operating Temperature | : 0°C ~ 45°C           |

E. & O.E.

## **DISTRIBUTED BY:**



**STRONG TECHNOLOGIES PTY LTD. - 60 WEDGEWOOD ROAD, HALLAM, VICTORIA 3803, AUSTRALIA**  
**PH: +61 3 8795-7990 FAX: +61 3 8795-7991**

**TECHNICAL SUPPORT: 1 800 8200 30**

**STRONG & CO. (FAR EAST), LTD. - P.O. BOX 85 YOKOHAMA, KANAGAWA-KEN - JAPAN 231-91 - FAX: +81 45 651-1842**

**www.strong-technologies.com**

**E-mail: [asales@strong-technologies.com](mailto:asales@strong-technologies.com)**