

Subwoofers

Power combined with Finesse.

Introduction

The Whatmough range of subwoofers all deliver crisp, deep bass to add a whole new exciting dimension to your music and movie soundtracks.

Tornado2 Subwoofer

The Tornado2 delivers impressive tight bass giving it exceptional musical abilities along with incredible dynamics essential for thrilling cinema sound experiences.

This is a true subwoofer, capable of producing deep and tight bass with absolute authority, and offering a level of musicality rarely found in a subwoofer at this price point.

As with all Whatmough Subwoofers, the Tornado is equally at home reproducing music or home cinema.



Tornado2 Subwoofer

Driver Configuration	10" Cellulose fibre coned long throw driver with a 50mm voice coil.
Enclosure	Fully sealed with 25mm thick cabinet walls
Amplifier	Class A/B 240 watts continuous power output. Line and speaker level inputs. Auto on/off switch. Continuously variable volume, phase and crossover frequency.
Bass Extension	23Hz -3db, usable bass to below 20 Hz
Dimensions	300W X 325H X 380D mm
Weight	22kg each
Finish	Black or Dark Cherry

Impulse2 Subwoofer

The Impulse2 subwoofer design acoustically rolls off at 24dB per octave above its cut off frequency of 100Hz. Total harmonic distortion is also reduced to the same extent when compared to a conventional direct radiator subwoofer whether it is sealed or vented. This means that the Impulse2 produces much lower amounts of harmonic distortion and therefore less degradation in the upper bass and midrange frequencies than conventional subwoofers. Not only will the bass sound cleaner and tighter, the upper bass and midrange will not be adversely influenced by this subwoofer. This is particularly important in a subwoofer designed to reproduce music and not just movie sound tracks.



The Impulse2 subwoofer is even cleaner and tighter than the original Impulse.

If you're serious about performance, love your music and movies, and loath compromise, this subwoofer was made for you.

Impulse2 Subwoofer

Driver	10" Cellulose fibre coned driver with extremely long linear excursion (36mm) and a huge 3" voice coil. This driver is capable of higher output than most 12" drivers.
Enclosure	25mm thick cabinet walls and extensively braced.
Amplifier	200 watts continuous power output. Line and speaker level inputs. Auto on/off switch. Continuously variable volume, phase and crossover frequency.
Bass Extension	23Hz -3db, usable bass down to below 20 Hz.
Dimensions	440H X 400W X 460D mm
Weight	34 kg
Finish	Bubinga (real wood veneer) or High Gloss Dark Graphite
Warranty	5 years